29566/KC15,412 Patent

SN: 09/834,682

In the Claims

Please cancel Claim 2 without prejudice and with right of re-entry into this application or any other appropriate application.

Kindly amend Claims 1, 3-5, 8-12, and 21 as follows.

1(Twice Amended). The personal care article as in Claim 8 wherein each of said outer portions of said first and second lateral sections is secured to one of said third and fourth side edges of said back portion to form a pant-like article having a waist opening, and first and second leg openings.

3(Amended). The personal care article as in Claim 1, including an absorbent core attached to at least one of said front portion, said back portion, and said crotch portion.

4(Amended). The personal care article as in Claim 1 wherein the attachment of the outer portions of the lateral sections to the front portion comprises at least one of adhesive bonds, ultrasonic bonds, thermally activated bonds, hook and loop fastening, snaps, buttons, tapes, needle punching, and piercing.

5(Amended). The personal care article as in Claim 1 wherein said first and second lateral sections generally overlie said front portion.

8(Twice Amended). A personal care article, having a longitudinal axis, and comprising:

(a) a front portion having a front end, a second end, a first side edge, and a second side edge;

29566/KC15,412 Patent

SN: 09/834,682

- (b) a first lateral section and a second lateral section, each of the first and second lateral sections having an inner portion releasably fastened to said front portion closer to the longitudinal axis than to the respective side edges, and an outer portion attached at at least one attachment site to said front portion, inwardly of, but adjacent the respective said first and second side edges, each of said first and second lateral sections being free from attachment to the front portion between the releasable fastening at the respective inner portion and areas adjacent the first and second side edges of the front portion;
- (c) a back portion having a back end, a third side edge and a fourth side edge; and
- (d) a crotch portion between said front portion and said back portion,

each of said outer portions of said first and second lateral sections being positioned on said front portion for securement to one of said third and fourth side edges of said back portion to form a pant-like article having a waist opening, and first and second leg openings,

strength of attachment, at said attachment sites, of said outer portions of said first and second lateral sections to said front portion being sufficiently weak that said attachments can be separated from said front portion without substantially fracturing said front portion.

9(Amended). The personal care article as in Claim 8, said outer portions of said first and second lateral sections each having an outer edge extending outwardly of the respective first and second side edges of said front portion whereby said first and second lateral sections are directly secured to respective ones of said third and fourth side edges of said back portion, without intervening material between said lateral sections and said back portion.

29566/KC15,412 Patent

SN: 09/834,682

10(Amended). The personal care article as in Claim 8, including an absorbent core attached to at least one of said front portion, said back portion, and said crotch portion.

11(Twice Amended). The personal care article as in Claim 8 wherein the attachment at the attachment sites between the outer portions of the lateral sections and the front portion comprises at least one of adhesive bonds, ultrasonic bonds, hook and loop fastening, snaps, buttons, tapes, needle punching, piercing, and thermally activated bonding.

12(Amended). The personal care article as in Claim 8 wherein said first and second lateral sections generally overlie said front portion.

21(Amended). The personal care article as in Claim 1 wherein strength of attachment of said inner portions of said first and second lateral sections to said front portion is less than strength of the securement of said outer portions of said first and second lateral sections to said back portion, whereby attachment of said inner portions of said first and second lateral sections to said front portion can be separated from said front portion without separating the securement of said first and second lateral sections from the third and fourth side edges of said back portion.

In the Drawings

Please amend FIGURES 1, 3, and 4 as submitted herewith.